



Castrol Ilocut 480 A

High Performance Neat Cutting Oil

Description

Castrol Ilocut™ 480 A is chlorine and heavy-metal free neat cutting oil especially formulated with a unique combination of lubricity additives and base oil to optimise machining performance, enhance surface finish and lower the overall operating costs. Ilocut 480 A is suitable for use in central systems as well as individual machines.

Application

Ilocut 480 A is designed for general machining of cast iron, steel and non-ferrous metals. It is especially recommended for use on small automatics, semi-automatics and multi-cut lathes.

Ilocut 480 A does not contain active sulphur and is compatible with yellow metals.

	Cast Iron	low-medium Alloyed Steel	High Alloyed Steel/Nickel-Chromium Alloys	Titanium Alloys	Aluminium Alloys	Yellow Metals
Honing/Superfinishing						
Grinding						
Drilling						
Broaching/Gear Manufacturing						
General Machining	√	√			√	√

Advantages

- Advanced additive technology gives high lubricity properties and lowers production costs through extended tool life.
- Improved surface finish and increased cutting speeds leads to improvement of process efficiency.
- Multi-metal machining using our superior additive technology provides opportunity for product consolidation.
- Our chlorine and heavy-metal free formulation improves the environmental profile and reduces disposal costs.

Typical Characteristics

Name	Method	Units	Ilocut 480 A
Appearance	Visual	-	Yellow
Viscosity at 40°C	DIN 51562	mm ² /s	14
Viscosity at 100°F	ASTM D446	mm ² /s	74
Density at 15°C	DIN 51757, ASTM D 1298	kg/m ³	866
	Calculated	lbs/gal	7.21
Flash Point COC	ISO 2592	°C	>170
	ASTM D92	°F	>338
Copper Corrosion, 3hrs at 100°C	ISO 2160, ASTM D 130		1a

Additional Information

	Ester	Active Sulphur	Inactive Sulphur	Phosphorous	Calcium	Chlorine	Zinc
Additives	√						

Castrol Ilocut 480 A

01 Mar 2011

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

www.castrol.com/industrial